


**Panel mounted inlet - Part no. 812**


- screw terminals
- nickel-plated contacts
- a retaining nose to hold the hinged lid of the connector must be provided by the customer in order to ensure satisfactory locking

**Technical information**

|                       |                 |
|-----------------------|-----------------|
| Ampere                | 16 A            |
| Poles                 | 3 p             |
| Voltage               | 230V            |
| Earth position        | 6 h             |
| Hertz                 | 50-60 Hz        |
| Connection technology | Screw terminals |
| Contact               | standard        |
| Protection type       | IP 44           |



| Drawing<br>2 MB 173/2 | Amp.<br>Poles   | 16   |      |      | 32   |      |      |
|-----------------------|---|------|------|------|------|------|------|
|                       |   | 3    | 4    | 5    | 3    | 4    | 5    |
| Dim. in mm            | a   | 85,7 | 85,7 | 85,7 | 85,7 | 85,7 | 85,7 |
|                       | b   | 85,7 | 85,7 | 85,7 | 85,7 | 85,7 | 85,7 |
|                       | c   | 72   | 72   | 72   | 90   | 90   | 90   |
|                       | d   | 69,5 | 69,5 | 69,5 | 69,5 | 69,5 | 69,5 |
|                       | e   | 69,5 | 69,5 | 69,5 | 69,5 | 69,5 | 69,5 |
|                       | f   | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  | 5,5  |
|                       | g.  | 11   | 11   | 11   | 11   | 11   | 11   |
|                       | g.1   | 2    | 2    | 2    | 2    | 2    | 2    |
|                       | l   | 32   | 36   | 36   | 47   | 47   | 47   |
|                       | Terminal for cond. cross section (mm <sup>2</sup> ) min.-max. | 1,5  | 1,5  | 1,5  | 2,5  | 2,5  | 2,5  |
|                       |   | -4   | -4   | -4   | -10  | -10  | -10  |